


Raimond II R127-R163-R199

RAIMOND PUTS




The Raimond lights: perfect spheres of mathematical ingredients punctuated by tiny LED lights. Designer Raimond Puts was intrigued by the shape of the geodesic dome and with the mystery of prime numbers. It's no coincidence that the dimension of all Raimond lights resembles a prime number. The result of mathematical perfection that brings the starry night sky into your home.

Detailing



Two steel spheres, interconnected with LEDs, form a thin and openwork triangular mesh that transport the electric current.


Colours



Stainless steel

Raimond II R127-R163-R199 / Raimond II, R127

Dimensions



Product

WIDTH 127cm | 50"
HEIGHT 127cm | 50"
DEPTH 127cm | 50"
DIAMETER 127cm | 50"
WEIGHT NETTO 4.5kg | 9.92lbs

Packaging

WIDTH 150cm | 59.1"
HEIGHT 150cm | 59.1"
CUBAGE 3.38m³ | 119.19ft³
LENGTH 150cm | 59.1"
WEIGHT 80.5kg | 177.47lbs

Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environments) with PMMA lenses

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

492

INPUT VOLTAGE

120-250V

FREQUENCY

50/60

MAX POWER CONSUMPTION

58W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

1000cm | 393.7"

CANOPY

White metal rectangle

COLOUR TEMPERATURE

2500 K

CRI

92

LIGHT DIRECTION

All directions

LIGHT OUTPUT

3390 lm

DIMMING & LIGHTING CONTROL


DALI dt6, Mains / ELV dimming is not possible

See last page for more information about the dimming possibilities.



Raimond II R127-R163-R199 / Raimond II, R163

Dimensions



Product

WIDTH 163cm | 64.2"
HEIGHT 163cm | 64.2"
DEPTH 163cm | 64.2"
DIAMETER 163cm | 64.2"
WEIGHT NETTO 7.5kg | 16.53lbs

Packaging

WIDTH 185cm | 72.8"
HEIGHT 185cm | 72.8"
CUBAGE 6.33m³ | 223.6ft³
LENGTH 185cm | 72.8"
WEIGHT 117.5kg | 259.04lbs

Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environments) with PMMA lenses

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

812

INPUT VOLTAGE

120-250V

FREQUENCY

50/60

MAX POWER CONSUMPTION

81W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

1000cm | 393.7"

CANOPY

White metal rectangle

COLOUR TEMPERATURE

2500 K

CRI

92

LIGHT DIRECTION

All directions

LIGHT OUTPUT

5596 lm

DIMMING & LIGHTING CONTROL


DALI dt6, Mains / ELV dimming is not possible

See last page for more information about the dimming possibilities.



Raimond II R127-R163-R199 / Raimond II, R199

Dimensions



Product

WIDTH 199cm | 78.3"
HEIGHT 199cm | 78.3"
DEPTH 199cm | 78.3"
DIAMETER 199cm | 78.3"
WEIGHT NETTO 12.5kg | 27.56lbs

Packaging

WIDTH 220cm | 86.6"
HEIGHT 220cm | 86.6"
CUBAGE 10.65m³ | 376.03ft³
LENGTH 220cm | 86.6"
WEIGHT 120kg | 264.55lbs

Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environments) with PMMA lenses

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1212

INPUT VOLTAGE

100-240V

FREQUENCY

50/60

MAX POWER CONSUMPTION

96W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

1000cm | 393.7"

CANOPY

White metal rectangle

COLOUR TEMPERATURE

2500 K

CRI

92

LIGHT DIRECTION

All directions

LIGHT OUTPUT

8354 lm

DIMMING & LIGHTING CONTROL

DALI dt6, Mains / ELV dimming is not possible

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

DALI dt6

The luminaire is dimmable by integrating it into a DALI network. This is an universal and professional standard in home automation systems with endless control possibilities and ease. We advise to hire a professional to integrate the luminaire into your DALI network.

Compatible models: Raimond II, R127 CE, Raimond II, R127 CU, Raimond II, R163 CE, Raimond II, R163 CU, Raimond II, R199 CE, Raimond II, R199 CU

Mains / ELV dimming is not possible

Mains and/or ELV dimming is not possible. The wireless wall switch is advised for dimming in this case.

Compatible models: Raimond II, R127 CE, Raimond II, R127 CU, Raimond II, R163 CE, Raimond II, R163 CU, Raimond II, R199 CE, Raimond II, R199 CU
